



## Omkami ATF III-H

### *Automatic Transmission Fluid*

Omkami ATF III-H is a quality automatic transmission fluid for use in a variety of passenger cars and light trucks. It is also recommended for on-highway and off-highway use in heavy duty automatic transmissions.

#### MEET PERFORMANCE STANDARDS

- GM Dexron III-H
- Ford MERCON
- Allison C-4

#### BENEFITS

- Provide protection for automatic gear box components
- Excellent oxidation stability
- Protection against wear, corrosion and foaming

#### TYPICAL APPLICATIONS

- Suitable for certain hydraulic systems
- Suitable in use for power steering units
- Do not use where GM Dexron VI or Ford Mercon, V/Mercon, SP/Mercon, LV Fluids are specified

#### TYPICAL PROPERTIES

SAE Grade	Test Method	ATF-III H
Viscosity Index	ASTM D2270	170
Kinematic Viscosity, mm <sup>2</sup> /s @ 40°C	ASTM D7042-16	36.6
Kinematic Viscosity, mm <sup>2</sup> /s @ 100°C	ASTM D7042-16	7.3
Density, kg/m <sup>3</sup> @ 15°C	ASTM D4052	0.850
Flash Point °C	ASTM D92	195
Pour Point °C	ASTM D97	-43

\*Typical properties do not constitute as specifications. Omkami reserves the right to amend and change the information herein without notification as result of continual product research and development.