



Omkami Super HD9

Ultimate Premium Heavy Duty Diesel Engine Oils

Omkami Super HD9 15W40 is specially developed to meet the new API CK-4 oil standard to better protect new and older engines using the “Low-Saps” additives package. It is designed to improve engine performance under severe conditions by providing enhanced protection against oil oxidation and engine wear. It can be used to lubricate a wide range of high speed diesel engines requiring API CK, CJ-4 and below required.

MEET PERFORMANCE STANDARDS

- API CK-4, CJ-4, CI-4
- ACEA E9
- CAT ECF-3
- Volvo VDS 4.5
- Cummins CES 20086

BENEFITS

- Rationalizes and minimizes fleet maintenance costs by reducing inventory needs in mixed fleets of different engines designs.
- Maintains lower levels of emissions and deposits that helps to control the blocking of the exhaust after treatment devices, thus maximizes the life of the catalyst metals and the cleaning intervals of the diesel particulate filters.
- Significant high level of wear protection than other oils that will prolong the engine efficiency and life

TYPICAL APPLICATIONS

- On and Off highway applications
- Commercial road vehicles including the latest engines fitted with exhaust clean-up devices of all types
- Suitable for use in agricultural and construction applications



TYPICAL PROPERTIES

SAE Grade	15W-40
Density,kg/Litre @ 15 °C	0.875
Kinematic Viscosity, mm ² /s @ 40 °C	115
Kinematic Viscosity, mm ² /s @ 100 °C	15.3
Viscosity Index	139
Pour Point, °C	-35
Flash Point COC, °C	236
Sulphated Ash (% , maximum)	1.0
TBN,mgKOH/g	10.1

*Typical properties do not constitute as specifications. Omkami reserves the right to amend and change the information herein without notification as result of continual product research and development.